



## 1. Applications

**Area:** LED Light use

**Purpose:** For Light Constant Current

**Features:**

- \* Universal AC Voltage.
- \* Ultra small size.
- \* Protections: Over voltage / Over current / Short.
- \* Non-isolation switching mode power Supply.
- \* Constant Current(+/- 3%).
- \* High Power Factor

## 2. Specification

NO	Description	
A	Model No.	CM-LDU SERIES(※ Chart 1)
B	Dimensions	L*89.3mm x W*26.2 mm x H*25.2 mm
C	POWER FACTOR	≥0.9
D	Weight	30g (no pour glue)
E	Operating Ambient Temperature	-20°C ~ 45°C
F	Input Voltage	90 ~ 264Vac (+/- 10%)50/60Hz(Universal)
G	Out Power	※ Chart 1
H	Protection	Short, OVP OCP OLP
I	Efficiency	85% Typical



全懋有限公司

CHUAN MO CORP.

TEL : 886-2-89816363

FAX : 886-2-89815353

DATE

REV


2013. 03. 24

1. 0

	LED DRIVE (CM-HV-4070C)	NO	
		PAGE	2/2

### 3. LED DRIVE SPEC (※ Chart 1)

Catalog Number	Input			Output			Application (VF-3.0VTypeical)
	Volts (V)	Pin max(W)	Current max(A)	Volts (V)	Po max(W)	Current max(mA)	
CM-HV-4070C	100~240	30	0.21	18~40V	28	700+/-5%	Series LED

	全懋有限公司	TEL : 886-2-89816363	DATE	2013. 03. 24
	CHUAN MO CORP.	FAX : 886-2-89815353	REV	1.0