



1. Applications

Area: LED Light use

Purpose: For Light Constant Current

Features:

- * Universal AC Voltage.
- * Ultra small size.
- * Protections: Over Temp .
- * Fully Isolated plastic case .
- * No isolation switching mode power supply.
- * Constant Current(+/- 10%).

2. Specification

NO	Description
A	Model No. CM-LDU-9935L(※ Chart 1)
B	Dimensions L*73mm x W*36mm x H*26mm
C	Casing Color Gray , No Case
D	Weight 130g
E	Operating Ambient Temperature -20 °C ~ 45 °C
F	Input Voltage 100 ~ 240Vac 50/60HZ(Universal)
G	Out Power ※ Chart 1
H	AC Input Wire Stock L 130mm 20 AWG
I	DC Output Wire Stock L 130mm 20 AWG
J	Protection OTP
K	Efficiency 85% Typical
L	
M	



全懋有限公司 TEL : 886-2-89816363

CHUAN MO CORP. FAX : 886-2-89815353

DATE

2008. 04. 22

REV

1.0

1. LED DRIVE SPEC (※ Chart 1)

Catalog Number	Input			Output			Application
	Volts (V)	Pin max(W)	Current max(A)	Volts (V)	Po max(W)	Current max(mA)	
CM-LDU-9935L	100~240	29	0.58	75	26	350+/-10%	



全懋有限公司 TEL : 886-2-89816363

CHUAN MO CORP. FAX : 886-2-89815353

DATE

2008.04.22

REV

1.0